




## Components

**Filter:** B05-1000  
**Lubricator:** 305-3000  
**Nipple:** Zinc Dichromate Coated Steel

Please see individual product pages for further details.



## Operating Specifications

- Bowl Capacity:** 8 oz.
- Maximum Pressure Ratings:**
  - Metal Bowl: 250 PSI
  - Polycarbonate Bowl: 150 PSI
- Temperature Ratings:**
  - Metal Bowls: 0-200°F
  - Polycarbonate Bowls: 0-120°F

## Features

- Filter, regulator and lubricator consolidated into one assembly
- Gauge included
- Push to lock bonnet assembly
- Black anodized finish standard
- Polycarbonate or aluminum bowls available
- Reduces footprint of air prep assembly
- Manual, float or impulse drains available
- Threaded bowls for ease of maintenance

## Ordering Information

### B3-1000-2

| Bowl Type                   |   |
|-----------------------------|---|
| Polycarbonate               | 0 |
| Polycarbonate w/ Bowl Guard | 1 |
| Metal                       | 2 |
| Metal w/ Sight Levels       | 3 |

| Pipe Size |   |
|-----------|---|
| 1/4"      | 2 |
| 3/8"      | 3 |
| 1/2"      | 4 |

| Elements  |   |
|-----------|---|
| 20 Micron | 0 |
| 10 Micron | 1 |
| 3 Micron  | 2 |

#### OPTIONS

| Anodizing         |       |
|-------------------|-------|
| None (Standard)   | Blank |
| Blue              | A1    |
| Black             | A2    |
| Clear             | A3    |
| Green             | A4    |
| Red               | A5    |
| Yellow            | A6    |
| Gold              | A7    |
| Purple            | A8    |
| Drain             |       |
| Manual (Standard) | Blank |
| Impulse           | D     |
| Float             | F     |
| Seals             |       |
| Buna-N (Standard) | Blank |
| Fluorocarbon      | V     |
| Attachment Part   |       |
| Bracket           | B     |


# FILTER REGULATOR/LUBRICATORS: FRL-1000



## Components

**Filter:** 205-1000  
**Regulator:** 104-1000  
**Lubricator:** 305-1000  
**Nipple:** Zinc Dichromate Coated Steel

Please see individual product pages for further details.



## Operating Specifications

- Bowl Capacity:** 8 oz.
- Maximum Pressure Ratings:**
  - Metal Bowl: 250 PSI
  - Polycarbonate Bowl: 150 PSI
- Temperature Ratings:**
  - Metal Bowls: 0-200°F
  - Polycarbonate Bowls: 0-120°F

## Features

- Filter, regulator and lubricator consolidated into one assembly
- Polycarbonate or aluminum bowls available
- Reduces footprint of air prep assembly
- Manual, float or impulse drains available
- Gauge included
- Threaded bowls for ease of maintenance

## Ordering Information

### FRL-1000-2

| Bowl Type                   |   |
|-----------------------------|---|
| Polycarbonate               | 0 |
| Polycarbonate w/ Bowl Guard | 1 |
| Metal                       | 2 |
| Metal w/ Sight Levels       | 3 |

| Pipe Size |   |
|-----------|---|
| 1/4"      | 2 |
| 3/8"      | 3 |
| 1/2"      | 4 |

| Elements  |   |
|-----------|---|
| 20 Micron | 0 |
| 10 Micron | 1 |
| 3 Micron  | 2 |

#### OPTIONS

| Anodizing         |       |
|-------------------|-------|
| None (Standard)   | Blank |
| Blue              | A1    |
| Black             | A2    |
| Clear             | A3    |
| Green             | A4    |
| Red               | A5    |
| Yellow            | A6    |
| Gold              | A7    |
| Purple            | A8    |
| Drain             |       |
| Manual (Standard) | Blank |
| Impulse           | D     |
| Float             | F     |
| Seals             |       |
| Buna-N (Standard) | Blank |
| Fluorocarbon      | V     |
| Attachment Part   |       |
| Bracket           | B     |
| Knob              | K     |